



Scan QR Code For
More Information



STANDARD PRODUCT PORTFOLIO

POKE-HOME CONTACT TECHNOLOGY

VERTICAL/HORIZONTAL | WIRE-TO-BOARD



KEY FEATURES:

- > Simple Strip and Poke-Home Wire Insertion
- > Reusable Twist & Pull Wire Extraction
- > Dual Beam Box Contact Provides Maximum Mechanical Stability and Wire Retention

CONNECTORS	Horizontal 9276-000	Low Profile Horizontal 9296-200	Horizontal 9296-400	Vertical 9296-500	Single Vertical 9296-600
# of Positions	1, 2, 3, 4, 6, 8	1, 2, 3, 4, 5, 6, 7, 8	1, 2, 3, 4, 5, 6	1, 2, 3, 4, 5, 6	1
Wire Gauge	18-26 AWG	20-26 AWG	18-24 AWG	18-26 AWG	18-22 AWG
Current Rating	Up to 6A/Contact	Up to 8A/Contact	Up to 10A/Contact	Up to 7A/Contact	Up to 8A
Voltage Rating	300 VAC	300 VAC	600 VAC	600 VAC 1p; 300 VAC 2p-6p	600 VAC
Operating Temp	-40°C to +125°C	-40°C to +130°C	-40°C to +130°C	-40°C to +130°C	-40°C to +130°C
UL Certification	UL 1977	UL 1977	UL 1977	UL 1977	UL 1977

STRIPT® CONTACTS	Single Horizontal Contacts 9296-000	Single Vertical Contacts 9296-100	Vertical Box Contact 9296-11X	BOARD-TO-BOARD JUMPERS	
				Ø0.80mm, Pitch 3mm 10-9296-X16	Ø1.00mm, Pitch 4mm 10-9296-X06
# of Positions	1	1	1	1, 2, 3	1, 2
Wire Gauge	12-28 AWG	18-26 AWG	12- 18 AWG	N/A	N/A
Current Rating	Up to 20A	Up to 15A/Contact	Up to 20A/Contact	Up to 5A/Pin	Up to 11A/Pin
Voltage Rating	300 VAC	300 VAC	300 VAC	300 VAC	300 VAC
Operating Temp	-40°C to +130°C	-40°C to +125°C	-40°C to 130°C	-40°C to +125°C	-40°C to +125°C
UL Certification	UL 1977	UL 1977	UL 1977	UL 1977	UL 1977