

TUNING KITS

Solder Plated, Nickel Barrier

Porcelain (+90)

Ceramic (NP0)

AQ12		AQ14		AQ12		AQ14	
Kit 1500 UZ		Kit 2500 UZ		Kit 1501 UZ		Kit 2501 UZ	
Capacitor Value pF	Tolerance*	Capacitor Value pF	Tolerance*	Capacitor Value pF	Tolerance*	Capacitor Value pF	Tolerance*
0.1	B	0.1	B	0.1	B	0.1	B
0.2	B	0.2	B	0.2	B	0.2	B
0.3	B	0.3	B	0.3	B	0.3	B
0.4	B	0.4	B	0.4	B	0.4	B
0.5	B	0.5	B	0.5	B	0.5	B
0.6	B	0.6	B	0.6	B	0.6	B
0.7	B	0.7	B	0.7	B	0.7	B
0.8	B	0.8	B	0.8	B	0.8	B
0.9	B	0.9	B	0.9	B	0.9	B
1.0	B	1.0	B	1.0	B	1.0	B
1.1	B	1.1	B	1.1	B	1.1	B
1.2	B	1.2	B	1.2	B	1.2	B
1.3	B	1.3	B	1.3	B	1.3	B
1.4	B	1.4	B	1.4	B	1.4	B
1.5	B	1.5	B	1.5	B	1.5	B
1.6	B	1.6	B	1.6	B	1.6	B
1.7	B	1.7	B	1.7	B	1.7	B
1.8	B	1.8	B	1.8	B	1.8	B
1.9	B	1.9	B	1.9	B	1.9	B
2.0	B	2.0	B	2.0	B	2.0	B
2.1	B	2.1	B	2.1	B	2.1	B
2.2	B	2.2	B	2.2	B	2.2	B
2.4	B	2.4	B	2.4	B	2.4	B
2.7	B	2.7	B	2.7	B	2.7	B
3.0	B	3.0	B	3.0	B	3.0	B
3.3	C	3.3	C	3.3	C	3.3	C
3.6	C	3.6	C	3.6	C	3.6	C
3.9	C	3.9	C	3.9	C	3.9	C
4.3	C	4.3	C	4.3	C	4.3	C
4.7	C	4.7	C	4.7	C	4.7	C
5.1	C	5.1	C	5.1	C	5.1	C
5.6	C	5.6	C	5.6	C	5.6	C
6.2	C	6.2	C	6.2	C	6.2	C
6.8	J	6.8	J	6.8	J	6.8	J
7.5	J	7.5	J	7.5	J	7.5	J
8.2	J	8.2	J	8.2	J	8.2	J
9.1	J	9.1	J	9.1	J	9.1	J
10.0	J	10.0	J	10.0	J	10.0	J

380 Capacitors 10 each of 38 values. All chips are laser marked.
 *Tolerance: B =±0.1pF, C =±0.25pF, J =±5%.

EVALUATION KITS

Solder Plated, Nickel Barrier

Porcelain (+90)

Ceramic (NP0)

AQ12

AQ14

AQ12

AQ14

Kit 1000 UZ	
Capacitor Value pF	Tolerance*
.5	B
1.0	B
1.2	B
1.5	B
1.8	B
2.0	B
2.2	B
2.4	C
2.7	C
3.0	C
3.3	C
3.6	C
3.9	C
4.3	C
4.7	C
6.8	J
8.2	J
10.0	J
12.0	J
15.0	J
18.0	J
22.0	J
27.0	J
33.0	J
39.0	J
47.0	J
56.0	J
68.0	J
82.0	J
100.0	J

300 Capacitors 10 each of 30 values.
All chips are laser marked.

*Tolerance: B = ± 0.1 pF, C = ± 0.25 pF, J = $\pm 5\%$.

Kit 2000 UZ	
Capacitor Value pF	Tolerance*
1.0	B
1.2	B
1.5	B
1.8	B
2.0	B
2.2	B
2.4	C
2.7	C
3.0	C
3.3	C
3.6	C
3.9	C
4.3	C
4.7	C
5.1	C
5.6	C
6.2	C
6.8	J
8.2	J
10.0	J
12.0	J
15.0	J
18.0	J
22.0	J
27.0	J
33.0	J
39.0	J
47.0	J
56.0	J
68.0	J
82.0	J
100.0	J
120.0	J
150.0	J
180.0	J
220.0	J
240.0	J
270.0	K
330.0	K
390.0	K
470.0	K
560.0	K
680.0	K
820.0	K
1000.0	K

450 Capacitors 10 each of 45 values.
All chips are laser marked.

*Tolerance: B = ± 0.1 pF, C = ± 0.25 pF, J = $\pm 5\%$, K = $\pm 10\%$

Kit 1001 UZ	
Capacitor Value pF	Tolerance*
.5	B
1.0	B
1.5	B
1.8	B
2.0	B
2.2	B
2.4	C
2.7	C
3.0	C
3.3	C
3.6	C
3.9	C
4.3	C
4.7	C
6.8	J
8.2	J
10.0	J
12.0	J
15.0	J
22.0	J
27.0	J
33.0	J
39.0	J
47.0	J
56.0	J
68.0	J
82.0	J
100.0	J
470.0	J
1000.0	J

300 Capacitors 10 each of 30 values.
All chips are laser marked.

*Tolerance: B = ± 0.1 pF, C = ± 0.25 pF, J = $\pm 5\%$.

Kit 2001 UZ	
Capacitor Value pF	Tolerance*
1.0	B
1.5	B
1.8	B
2.0	B
2.2	B
2.4	C
2.7	C
3.0	C
3.3	C
3.6	C
3.9	C
4.3	C
4.7	C
5.1	C
5.6	C
6.2	C
6.8	J
8.2	J
10.0	J
12.0	J
15.0	J
22.0	J
27.0	J
33.0	J
39.0	J
47.0	J
56.0	J
68.0	J
82.0	J
100.0	J
120.0	J
150.0	J
180.0	J
220.0	J
240.0	J
270.0	K
330.0	K
390.0	K
470.0	K
560.0	K
680.0	K
820.0	K
1000.0	K
2700.0	K
5100.0	K

450 Capacitors 10 each of 45 values.
All chips are laser marked.

*Tolerance: B = ± 0.1 pF, C = ± 0.25 pF, J = $\pm 5\%$, K = $\pm 10\%$

NOTE: Order by Kit Number
Example: Kit 1000 UZ